

# CRYSTAL CLEAR® SEAL WB



## Product Description

CRYSTAL CLEAR® SEAL WB is a water-based uv-stable concrete curing and sealing compound formulated using styrene-acrylate resin. CRYSTAL CLEAR® SEAL WB is used for curing and sealing of all types of cementitious based substrates. The high quality film-forming qualities of CRYSTAL CLEAR® SEAL WB make it an ideal product for interior or exterior use on all types of flooring, walls, pavements, and parking decks.

## Installation

Before using this product, please refer to the Material Safety Data Sheet for additional information. Proper handling precautions MUST be followed. The conditions of use, handling, and application of this product and information (whether verbal or written), including any suggested formulations and recommendations, are beyond Lambert Corporation's control. Therefore, it is imperative that testing be performed to determine satisfaction and suitability for intended use and health, safety, and environmental issues. The following information is meant as a guideline of best industry practices. While Lambert Corporation does suggest adherence to these guidelines, unforeseeable variables and/or developed successful installer practices may cause variation in methods and/or results.

## Surface Preparation

Surfaces must be thoroughly cleaned, dry, and free of all debris and standing water. Contact Lambert Corporation for recommendations on the removal of pre-existing products that may cause adhesion issues with CRYSTAL CLEAR® SEAL WB. Always apply sample area to determine bond and compatibility.

## Mixing

Do not dilute or alter product. Always agitate liquid curing and sealing compounds thoroughly prior to use.

## Application

Apply a uniform film, at 200-400 ft<sup>2</sup> per gallon (4.9-9.8m<sup>2</sup>/L) depending upon porosity of surface, with approved LAMBCO® SPRAYER (see LAMBCO® SPRAYER Technical Data Sheet), brush, or roller, with smooth concrete requiring lamb's wool applicator or short-nap roller. For new concrete, apply as soon as possible following final finish of substrate. Apply second application immediately following the completion of all project work to be performed on or over the surface for best performance. Curing compounds such as CRYSTAL CLEAR® SEAL WB, when applied at lower temperatures, such as 40-50°F (4-10°C), will appear cloudy or whitish but will clear upon drying.


## Limitations

Keep from freezing. DO NOT apply when concrete surfaces or ambient temperatures are below 50°F (10°C). Allow for proper ventilation of project area, both during and following application of CRYSTAL CLEAR® SEAL WB. Cementitious overlays and toppings will not bond

to CRYSTAL CLEAR® SEAL WB treated surfaces. CRYSTAL CLEAR® SEAL WB should never be applied over standing water, bituminous asphalt, resilient tiles, or areas to be caulked with elastomeric joint sealants. DO NOT apply in conditions where rain is forecasted within 48-hours following application. DO NOT apply in presence of areas containing comestibles; remove all such items prior to use. Application of curing and sealing compounds such as CRYSTAL CLEAR® SEAL WB can affect skid resistance of surfaces. In areas such as pool and patio decks that will come into contact frequently with water, it is best to add LAMBCO® TEXT (see LAMBCO® TEXT Technical Data Sheet) texturing additive.

## Technical Information

CRYSTAL CLEAR® SEAL WB will offer temporary protection to aliphatic solvent spillages but is not designed for areas where continuous spillages of petroleum products may be expected.

 www.LambertUSA.com	<b>Packaging:</b>
5-GALLONS (19 Liters)	5-Gallons (18.9-Liters) Pail
55-GALLONS (208.2-Liters)	55-Gallons (208.2-Liters) Drum
270-GALLONS (1022-Liters)	270-Gallons (1022-Liters) Tote

**CRYSTAL CLEAR® SEAL WB**  
Water-Based Cure-and-Seal Compound

FOR INDUSTRIAL USE ONLY  
Review Product Data & Material Safety Data Sheets (MSDS) prior to using. Do not use until completely familiar with instructions for use.  
VOC RATING: NON-HAZARDOUS  
EXPRESS LIMITED WARRANTY AND LIMITATION OF LIABILITY  
This information is provided as a guide only and does not constitute a contract.



## Applicable Standards

ASTM C-309 - Type 1 - Class A&B  
AASHTO M148 - Type 1 - Clear

CRYSTAL CLEAR SEAL WB

Solid Content	18% by Weight	
Dry Time - 65-85°F (18.3-29.4°C)	Tack Free	60 Minutes
	Light Traffic	2-4 Hours
	Normal Traffic	24-36 Hours
	Maximum Hardness	72 Hours

Chemical Resistance	10% Sulfuric Acid	Excellent
	10% Hydrochloric Acid	Excellent
	10% Nitric Acid	Good
	40% Sodium Hydroxide	Good
	100% Vegetable Oil	Excellent
	100% Mineral Oil	Excellent
	Aliphatic Solvents	Good
	Hydraulic Oil	Poor
	Aromatic Solvents	Poor
	Gasoline	Poor

### Coverage

200-400 ft<sup>2</sup> per gallon (4.9-9.8m<sup>2</sup>/L) depending upon porosity of surface

### Clean-Up

Refer to CRYSTAL CLEAR® SEAL WB Material Safety Data Sheet where applicable. Clean tools, LAMBCO® SPRAYERS, and other equipment as suggested by manufacturer.

### First Aid

Avoid contact with skin and wash exposed skin areas promptly with soap and water. If any product gets into eyes, rinse immediately and repeatedly with water and get prompt medical attention. Avoid overexposure to the airborne dust. If inhalation occurs, remove to fresh air area and seek medical attention if required. Refer to product Material Safety Data Sheet for further information.

### VOC Content

99.3-g/L or 0.83-lbs/gal less exempt content

**KEEP OUT OF REACH OF CHILDREN. FOR INDUSTRIAL USE ONLY.**

CURE & SEAL PRODUCTS